



注記
NOTES

- 材料:
MATERIALS:
ウエハー: ガラス入り 66ナイロン
UL94V-0 色: グレー
WAFER: GLASS FILLED 66 NYLON
UL94V-0, COLOR: GRAY
ピン: 黄銅、スズメッキ
PIN: BRASS, PRE-TINNED
- 適合メスコネクター: 51089-***5, 52478-***15,
MATING CONNECTORS:
- 推奨基板厚: RECOMMENDED PCB THICKNESS: t
イジェクターが開いている状態。
EJECTORS IN OPEN POSITION
- メッキ仕様
TERMINAL PLATING
表面メッキ: スズメッキ 14μm MIN.
SURFACE PLATE: TIN 14μm MIN.
下地メッキ: ニッケルメッキ 0.54μm MIN.
UNDER PLATE: NICKEL 0.54μm MIN.

無鉛
LEAD FREE

80.4	71.4	63.6	58	53314-6065	60
70.4	61.4	53.6	48	-5065	50
60.4	51.4	43.6	38	-4065	40
54.4	45.4	37.6	32	-3465	34
50.4	41.4	33.6	28	53314-3065	30
(D)	C	B	(A)	MATERIAL NO.	CKT.

REVISED EC NO: J2007-0432 DRWNG: KAITO01 2006/08/11 CHKD: THARUYAMA 2006/08/21 APPR: NUKITA 2006/08/23	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 2:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
	10 UNDER	±0.2	DRAWN BY A. IDA		DATE 2003/05/07		
	10 OVER 30 UNDER	±0.25	CHECKED BY J. MIYAZAWA		DATE 2003/05/07		
	30 OVER	±0.3	APPROVED BY Y. ITO		DATE 2003/05/07		
	ANGULAR	±3 °	MATERIAL NO. SEE CHART		DOCUMENT NO. SD-53314-001		SHEET NO. 1 OF 1
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		TITLE 2.0 W/B DUAL ROW S/T HEADER WITH EJECT ASSY MOLEX INCORPORATED					
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							

MATERIAL 材料
注記参照
SEE NOTES