



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
02 ₁	SEE ECN 80-0084	GB 1/22/80	TS 1/23/80
03 ₀	CHANGED REV PER ECN 88-0651	GS 3/24/88	
03 ₁	REDRAWN IN CAD, ECN 88-0678	<i>OGM</i> 10/7/91	<i>BB</i> 10/9/91

HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
COMPONENT	MATERIAL	FINISH

CABLE ENTRY DIAMETER MINIMUM		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON			DRAWN BY ES 3/14/68		DATE		AMP Incorporated		
HOUSING	.089	FRAC.	DEC.	ANGLES	CHECKED BY	PRB	3/14/68	AMP		140 Fourth Avenue Waltham, MA 02451-7599	
CONTACT	.023	$\pm 1/64$	$\pm .005$	$\pm 1^\circ$	APPRD BY	D.NANIA	3/14/68				
		These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.			USE ASS'Y PROCEDURE		TITLE		OSSM STRAIGHT CABLE PLUG DIRECT SOLDER ATTACHMENT		
					NO. AP. 10-002		SIZE	CODE IDENT NO.	1001-5004-00	REV	03 ₁
					408-04795		B	26805			SHEET 1 OF 1
							SCALE	8:1			

NOTES:
1. DESIGNED FOR USE WITH .085 DIA SEMI-RIGID CABLE