

## Specification Sheet

Part Number: 596-00613

**CAUTION: SOLAR ELECTRIC  
SYSTEM CONNECTED**

Solar Label, Reflective, CAUTION SOLAR ELECTRIC SYSTEM CONNECTED, 6.5" x 1.0", Yellow, 50/roll

Article Number	596-00613
Type	CSESC
Color	Yellow (YE)
Features & Benefits	<ul style="list-style-type: none"><li>• Made with UV stable inks and materials for durability and weather resistance</li><li>• Supplied with aggressive adhesive to ensure long life</li><li>• Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections</li><li>• Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers</li></ul>
Quantity Per	roll

**Product Description**

HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Short Description**

Solar Label, Reflective, CAUTION SOLAR ELECTRIC SYSTEM CONNECTED, 6.5" x 1.0", Yellow, 50/roll

**Global Part Name**

CSESC-242/552-YE

**Technical Description**

Pre-Printed Solar Label, Reflective, "SOLAR ELECTRIC SYSTEM CONNECTED", 6.5" X 1.0", Yellow

**Local Order Number 2**

Cross Reference = 10 per pack: 596-00672; Spanish version 50 per roll: 596-00821

**Width W (Imperial)**

6.5

**Width W (Metric)**

165.1

**Thickness T (Metric)**

64.0

**Height H (Imperial)**

1.0

**Height H (Metric)**

25.4

**Material**

Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate

**Material Shortcut**

242/552

<b>Adhesive</b>	Acrylic
<b>Halogen free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature (Metric)</b>	-40°F to +174°F (-40°C to +79°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	NEC2014 ANSI Standard Z535.4 NEC2011 IFC 2012 UL 969
<b>Warranty (US)</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	50
<b>Package Quantity (Metric)</b>	50
<b>Customs Number</b>	3919905060
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	.104
<b>Weight (Imperial)</b>	0.23

---

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)