



| CODE NO. | NUMBER OF CONTACT | A | B | C | D | E |
|------------|-------------------|------|------|------|------|------|
| 541-0943-0 | 2 | 8.0 | 2.5 | 15.0 | 8.4 | 11.9 |
| 541-0944-3 | 3 | 10.5 | 5.0 | 17.5 | 10.9 | 14.4 |
| 541-0945-6 | 4 | 13.0 | 7.5 | 20.0 | 13.4 | 16.9 |
| 541-0946-9 | 5 | 15.5 | 10.0 | 22.5 | 15.9 | 19.4 |
| 541-0947-1 | 6 | 18.0 | 12.5 | 25.0 | 18.4 | 21.9 |
| 541-0948-4 | 7 | 20.5 | 15.0 | 27.5 | 20.9 | 24.4 |
| 541-0949-7 | 8 | 23.0 | 17.5 | 30.0 | 23.4 | 26.9 |
| 541-0950-6 | 9 | 25.5 | 20.0 | 32.5 | 25.9 | 29.4 |
| 541-0951-9 | 10 | 28.0 | 22.5 | 35.0 | 28.4 | 31.9 |

| APPLICABLE PANEL THICKNESS(t) | X |
|-------------------------------|-----|
| 1.7-2.0 | 1.5 |
| 1.3-1.6 | 1.0 |
| 0.9-1.2 | 0.5 |
| 0.7-0.8 | 0 |

NOTES
 ① : SHOWS CONFIGURATION OF THE MATING FACE FOR 2, 3, 4 AND 5 POS.
 ② : INDICATED CONFIGURATION IS APPLICABLE TO 6 POS., AND HIGHER CONTACT POSITIONS.
 ③ : INDICATED CONFIGURATION IS APPLICABLE TO 8 POS., AND HIGHER CONTACT POSITIONS.
 ④ : USE THE SHARP EDGE FOR ENGAGEMENT WITH THE PANEL.

| NO. | MATERIAL | FINISH . REMARKS | NO. | MATERIAL | FINISH . REMARKS |
|-----|-----------|------------------|-----|-------------------------|------------------|
| 1 | POLYAMIDE | | | WHITE(NATURAL), UL94V-0 | |

| UNITS | SCALE | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|-------|-------|-------|--------------------------|----------|---------|------|
| mm | 2 : 1 | △ | | | | |

| | | | |
|-------------------------|----------|-------------|----------------|
| APPROVED : TS. SAKATA | 10.02.16 | DRAWING NO. | EDC3-161949-02 |
| CHECKED : TS. FUKUSHIMA | 10.02.16 | PART NO. | DF1E-*EP-2.5C |
| DESIGNED : HT. SATO | 10.02.10 | CODE NO. | CL541- |
| DRAWN : YK. NAKATSU | 10.02.09 | | |