


示意图 SCHEMATIC



安装孔 PIERCING PLAN

规格 Specifications

额定负荷 Ratings	DC 30 V 100m A
初始接触电阻 Initial Contact Resistance	200 mΩ Max.
绝缘电阻 Insulation Resistance	DC250 V.60 Sec.10 MΩ Min.
抗电强度 Dielectric Voltage	AC 250 V(50~60HZ) 60 Sec.
操作力 Operationg Force(gf)	30±20 gf
自由位置 Free Position	5.20mm Max
动作位置 Operationg Position	3.20±0.40mm
超行程 Over Travel	2.00±0.40mm
负荷寿命 Operationg Life With Load	20,000 Cycles

7	端子	TERMINAL	C2680R (b)	3	Ag PLATED	A03	零件材料标示变更见 (b)	曹文斌	2006-03-20
6	胶壳	HOUSING	PA46 (b)	1	BLACK C		机械寿命变更为负荷寿命见 (b)		
5	弹簧	SPRING (b)	SUS	1	NATURAL		追加零件标示见 (b)		
4	接触片	CONTACT CLIP (b)	C5210R	1	Ag CLAD	A02	PA 1300G011 变更为 PA46 TE250F6-BK 见 (c)	曹文斌	2006-01-21
3	滑块	SLIDER (b)	PBT	1	BLACK C		3.30 变更为 3.70 见 (c)		
2	胶盖	COVER	PA46 (b)	1	BLACK C	A01		曹文斌	2005-12-30
1	胶柄	KNOB	POM (b)	1	BLACK C	标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
序 NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	DWG NO. ITEM2383				

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	DETECTOR SWITCH		ITEM NO	DS-080-C PA			
UNDER 1	± 0.10	DRAWN	曹文斌	2006-03-20	VERSION	A03	PAGE	1	OF 1
1 - 10	± 0.30	REVIEWED	张念明	2006-03-20	SCALE	NO SCALE	UNIT	mm	
OVER 10	± 0.50	APPROVED	林高全	2006-03-21	PROJECTION				

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.