



CRYSTEK
MICROWAVE
A DIVISION OF CRYSTEK CORPORATION

18 GHz HAND FORMABLE .141 COAX CABLES

50 Ohm DC-18 GHz Hand Formable Coaxial Cables



Features:

- Center Conductor:** Silver-plated copper clad steel wire
- Outer Braid:** Tin-soaked copper braid, 100% coverage
- Insulation:** PTFE (Polytetrafluoroethylene) dielectric
- Cable Outer Dia.:** 0.141 (3.58mm)
- Connectors:** Gold plated brass
- Center Pin:** Gold plated brass
- Operating Temperature:** -40°C to +85°C
- Minimum Bend Radius:** 0.39" (10mm) single bend
1.57" (40mm) multiple bends

Electrical Specifications:


- Impedance:** 50 Ohms
 - Frequency:** DC to 18 GHz
 - Insertion Loss:** <.67 dB/ft at 18 GHz
 - VSWR:** <1.3, DC to 18 GHz
 - Nominal Capacitance:** 28.6 pF/ft
 - Velocity of Propagation:** 70%
 - RF Shielding:** < -130 dB Typical
 - Attenuation (dB/ft):** 0.12 Typ. at 1 GHz
0.23 Typ. at 3 GHz
0.31 Typ. at 5 GHz
0.46 Typ. at 10 GHz
0.65 Typ. at 18 GHz
- *connector loss not included
(refer to actual cable plot (see below))

- Avg Power in (Watts):** 686 @ 400 MHz
419 @ 1 GHz
122 @ 10 GHz
83 @ 18 GHz
- *as specified at 40°C

Custom Lengths Available

Electrically Matched Pairs Available

Actual Plot



- Applications:** Jumpers
Instrumentation
High Frequency Interconnects



SMA / SMA [Straight/Straight]

Part Number	Description	Length
CCSMA18-MM-141-3	.141 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	3"
CCSMA18-MM-141-4	.141 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	4"
CCSMA18-MM-141-5	.141 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	5"
CCSMA18-MM-141-6	.141 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	6"
CCSMA18-MM-141-7	.141 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	7"
CCSMA18-MM-141-8	.141 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	8"
CCSMA18-MM-141-10	.141 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	10"
CCSMA18-MM-141-12	.141 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	12"



CRYSTEK
CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FL 33913

PHONE: 239-561-3311 • 800-237-3061 Rev.: A

FAX: 239-561-1025 • WWW.CRYSTEK.COM Date: 07-29-11