

3M™ Cold Shrink End Caps EC-Series

Data Sheet

November 2013



Description

3M Cold Shrink End Caps are close-ended, tubular rubber sleeves that are factory expanded and loaded onto a removable core. When positioned over the end of a cable, or other cylindrical object, the core is removed to provide a reliable environmental seal. Four different end caps are available to accommodate a wide range of sizes.

Agency Approvals & Self Certifications


RoHS
2011/65/EU

"RoHS 2011/65/EU" means that the product or part does not contain any of the substances in excess of the maximum concentration values ("MCVs") in EU RoHS Directive 2011/65/EU. The MCVs are by weight in homogeneous materials. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

EHS

CAUTION

Working around energized systems may cause serious injury or death. Installation should be performed by personnel familiar with good safety practice in handling electrical equipment. De-energize and ground all electrical systems

- 3M Cold Shrink Removable Core is a mixed polymer and recyclable with waste. 
- Read all Health Hazard, Precautionary and First Aid statements found in the Material Safety Data Sheet (MSDS) and/or product label prior to handling or use.

Applications

Moisture sealing and physical protection for cables, pipes or other cylindrical objects.

3M™ Cold Shrink End Caps EC-Series

Features

- Simple and fast installation, no tools required
 - Accommodates size ranges from 0.46" -3.32"
 - Good abrasion resistance
 - Seals tight, retains resiliency for years
 - Water resistant
 - No mastic or tape required
 - Resists acids and alkalis
 - Resists ozone
 - Easy removal
-

Typical Physical Properties

Not for specifications. Values are typical, not to be considered minimum or maximum. Properties measured at room temperature 73°F (~23°C) unless otherwise stated.

EPDM Rubber

Physical Property (Test Method)	Typical Value US units (metric)
Color	Black
300% Modulus (ASTM D 412-87)	480 psi (3,3 MPa)
Ultimate Tensile (ASTM D 412-87)	1400 psi (9,6 MPa)
Ultimate Elongation (ASTM D 412-87)	750%
Die C Tear (ASTM G-21)	150 pli (26,3 KN/m)
Moisture Absorption - 7 days in H ₂ O	Wt. Gain 1.8%

Selection Chart

Product #	Use Range	
	inches	(mm)
EC-1	0.46 - 0.82	(11,6 - 20,9)
EC-2	0.63 - 1.18	(15,9 - 30,1)
EC-3	1.02 - 1.94	(26,0 - 49,2)
EC-4	1.79 - 3.32	(45,5 - 84,3)

Maintenance

3M Cold Shrink End Caps EC-Series are stable under normal storage conditions. The end caps are not impaired by freezing or overheating due to ambient temperatures encountered during shipping or storage. Normal storage and stock rotation are recommended.

3M™ Cold Shrink End Caps EC-Series

Shelf Life & Storage	This product has a 5-year shelf life from date of manufacture when stored in a humidity controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).
Availability	Please contact your local distributor; available from 3M.com/electrical [Where to Buy] or call 1.800.245.3573.

3M, Super 33+ and Scotch are trademarks of 3M Company.

Important Notice	All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product, which are not contained in 3M's current publications, or any contrary statements contained on your purchase order, shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.
-------------------------	---

Warranty; Limited Remedy; Limited Liability	This product will be free from defects in material and manufacture at the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.
--	---



Electrical Markets Division
6801 River Place Blvd.
Austin, TX 78726-9000
800.245.3573
FAX: 800.245.0329
www.3M.com/electrical

Please recycle
© 3M 2013 All rights reserved
78-8125-9558-1 Rev B