




Date	SYM	REVISION RECORD	AUTH	DR.	CK.
02/01/03	A	(1) 23.50 was 31.00. (2) 8.50 was 9.50 (3) added dimple on jack	T.B.	B.S.	
04/20/12	B	Wire gauge 22AWG was 24AWG	T.B.	B.S.	
04/27/12	C	Added "ROHS COMPLIANT"	T.B.	B.S.	
05/25/12	D	Added Max. Rating	T.B.	B.S.	



HOUSING: BLACK  
 CORD: UL2468, 300V, 80°C, 22 AWG  
 PASSES UL FLAME TEST VW-1  
 CENTER IS POSITIVE CONTACT  
 DC MOLDED PLUG: 2.5mm X 5.5mm  
 VOLTAGE RATING: 24VDC  
 MAX. RATINGS OF VOLTAGE: 300V  
 MAX. RATINGS OF CURRENT: 3AMP  
 ROHS COMPLIANT

Tolerance (Inches)	 Memory Protection Devices, Inc. 200 Broad Hollow Road, Farmingdale, New York 11735		
Decimal ±.5 (.020)	Scale	Drawn By B.S. Approved By T.B.	
Fractional ± .8 (.030)	Title 2.5mm DC MOLDED PLUG WITH 10' WIRE LEADS		
Angular ± 3°	Date 05/25/12	Drawing Number 172-1018	