



RECOMMENDED PC BOARD LAYOUT

- 1 NYLON, UL 94V-0 RATED, RED.
- 2 BRASS PER ASTM B36.
- 3 3.81um [.000150] MIN TIN OVER 2.54um [.000100] MIN COPPER.
- 4 0.76um [.000030] MIN GOLD FOR A LENGTH OF 5.08 [.200] FROM MATING END, 3.81um [.000150] MIN TIN-LEAD FOR A LENGTH OF 4.83 [.190] MIN FROM OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL.
- 5 .000150 MIN TIN OVER .000100 MIN CU, OR .000050 MIN NICKEL.
- 6 0.76um [.000030] MIN GOLD FOR A LENGTH OF 5.08 [.200] FROM MATING END, 3.81um [.000150] MIN TIN FOR A LENGTH OF 4.83 [.190] MIN FROM OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL.

6	NO	1-207121-0
6	YES	207121-9
5	YES	207121-8
4	NO	207121-4
4	YES	207121-3
3	NO	207121-2
3	YES	207121-1
CONTACT FINISH		MOUNTING TABS
		PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN L.SIPE 03/12/92	APVD R.STONE 3-17-92
0 PLC ± -	1 PLC ± -	NAME A. TRAVIS 3-17-92	PRODUCT SPEC 108-10033
2 PLC ± 0.13 [.005]	3 PLC ± -	SIZE A1	SCALE 4:1
4 PLC ± -	ANGLES ± -	WEIGHT -	SHEET 1 OF 1
MATERIAL HOUSING 1	FINISH CONTACT: SEE TABLE	RESTRICTED TO -	REV Y2

CUSTOMER DRAWING