

Specification Sheet

Part Number: 111-01235



Article Number

111-01235

Type

PT220

Color

Beige (BGE)

Features & Benefits

- Extreme temperature range for excellent performance in a range of environments.
- Low-profile, contoured head takes up less space and protects sensitive wires.
- Delivers the performance of a metal tie with the ease of use of plastic.

Quantity Per

bag

Product Description

PEEK Ties withstand temperatures from -67 to 464 degrees F and provide excellent resistance to chemicals, acids, radiation and abrasion. The low-profile, contoured head takes up less space and protects sensitive wires running adjacent to it.

Short Description

High-Temp Cable Tie, 8.7" Long, 85lb Tensile Strength, PEEK, Beige, 100/pkg

Global Part Name

PT220-PEEK-BGE

Minimum Tensile Strength (Imperial)

85.0

Minimum Tensile Strength (Metric)

380.0

Length L (Imperial)

8.7

Length L (Metric)

220.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.19

Width W (Metric)

4.7

Bundle Diameter Min (Imperial)

0.32

Bundle Diameter Min (Metric)

8.0

Bundle Diameter Max (Imperial)

2.2

Bundle Diameter Max (Metric)

56.0

Thickness T (Imperial)

0.05

Thickness T (Metric)

1.3

Cable Tie Head Length (Imperial)

0.28

Cable Tie Head Width (Imperial)

0.32

Material

Polyetheretherketone (PEEK)

Material Shortcut

PEEK

Flammability

UL 94 V0

Halogen free

Yes

Operating Temperature (Metric)

-67°F to +464°F (-55°C to +240°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

DNV GL | EN 62275:2009 VDE | DIN EN 62275:2016-01

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909987

Content Unit(BMEcat)

pcs.

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)