



NUMBER OF POSITIONS	DIMENSION	
	A	B
06	4.0	11.2
08	6.0	13.2
10	8.0	15.2
12	10.0	17.2
14	12.0	19.2
16	14.0	21.2
18	16.0	23.2
20	18.0	25.2
22	20.0	27.2
24	22.0	29.2
26	24.0	31.2
28	26.0	33.2
30	28.0	35.2
32	30.0	37.2
34	32.0	39.2
36	34.0	41.2
38	36.0	43.2
40	38.0	45.2
44	42.0	49.2
48	46.0	53.2
50	48.0	55.2
54	52.0	59.2
56	54.0	61.2
60	58.0	65.2
62	60.0	67.2
64	62.0	69.2
68	66.0	73.2
80	78.0	85.2

MATERILA&FINISH
 insulator:PBT Glass Fiber(UL94V-0)BLAKC
 Contact:Brass

Contact:Gold-Plated Over Nickel
 SPECIFICATIONS

Current Rating:1A AV,DC
 Voltage Rating:250V AC,DC
 Temperature Range:-40°C TO +150°C
 Contact Resistance:20mΩ Min
 Insulation Resistance:1000mΩ Min
 withstanding Voltage:500V AC/Min

UNLESS OTHERWISE SPECIFIED TOLERANCE :		CnC Tech ,LLC Industrial Cable and Connector Technology			
X.	±0.20				
X.X	±0.15	DO NOT SCALE DRAWING		PART NO. 3130-01-XX-0104	
X.XX	±0.10			SIZE A	UNIT MM
DRAWN BY				TITLE 2.0/IDC	
CHECKED BY				REV	B0
APPROVED BY	FNLIU.bmp	SCALE		THIRD ANGLE PROJECTION	PAGE 1 OF 1
DWG NO.				ITEM NO.	DATE 2005/07/17