


On phase-out, not recommended for new designs



60.0VDC · 1.1 - 3.75A



**Description**

- PFRY is recommended as substitute

**Standards**

- UL 1434  
- CSA C22.2 no. 0, TIL no. CA-3A

**Approvals**

- UL File Number: E172175

**Applications**

- Security and fire alarm systems  
- Loud speakers  
- Power transformers

**References**

[Packaging Details](#)



**Weblinks**

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

**Technical Data**

V max	60.0VDC	Soldering Methods	Wave
I <sub>max</sub>	40A	Solderability	235 °C / 2 sec
I hold	1.1 - 3.75A	Resistance to Soldering Heat	260 °C / 10 sec
Mounting	PCB, THT	Passing Aging	+85 °C, 1000 Hours -> +/- 5% Typical Resistance Change
Allowable Operation Temp.	-40 °C to 85 °C	Humidity Aging	+85 °C, 85% r.h., 1000 Hours -> +/- 5% Typical Resistance Change
Material: Terminals	Tin-Plated Copper	Thermal Shock	MIL-STD-202, Method 107 (+125 °C to -55 °C, 10 Cycles) -> +/- 15% Typical Resistance Change
Weight	0.35 g	Vibration	MIL-STD-883C, Method 2007.1, Test Condition A
Storage Conditions	0 °C to 40 °C, max. 70% r.h.	Resistance to Solvents	MIL-STD-202, Methode 215
Product Marking	Type, I hold	Flammability	UL 94V-0

**Dimensions**



PFRA.010 - PFRA.185

Drilling diagram

### Dimensions

A max [mm]	Insert depth	C min [mm]	C max [mm]	D min [mm]	E max [mm]	Ø Lead [mm]	Order Number
13	18	4.4	5.1	7.6	3.1	0.81	PFRX.110
14.5	19.6	4.4	5.1	7.6	3.1	0.81	PFRX.135
16.3	21.3	4.4	5.1	7.6	3.1	0.81	PFRX.160
17.8	22.9	4.4	5.1	7.6	3.1	0.81	PFRX.185
21.3	26.4	9.5	10.2	7.6	3.1	0.81	PFRX.250
24.9	30	9.5	10.2	7.6	3.1	0.81	PFRX.300
28.4	33.5	9.5	10.2	7.6	3.1	0.81	PFRX.375

### Thermal Derating Chart Ihold [A]

-40 °C	-20 °C	0 °C	23 °C	40 °C	50 °C	60 °C	70 °C	85 °C	Order Number
1.71	1.5	1.31	1.1	0.89	0.79	0.69	0.59	0.44	PFRX.110
2.09	1.84	1.61	1.35	1.09	0.97	0.85	0.73	0.54	PFRX.135
2.48	2.18	1.9	1.6	1.3	1.15	1.01	0.86	0.64	PFRX.160
2.87	2.52	2.2	1.85	1.5	1.33	1.17	1	0.74	PFRX.185
3.88	3.4	2.98	2.5	2.03	1.8	1.58	1.35	1	PFRX.250
4.65	4.08	3.57	3	2.43	2.16	1.89	1.62	1.2	PFRX.300
5.81	5.1	4.46	3.75	3.04	2.7	2.36	2.03	1.5	PFRX.375

### Electrical Characteristics at 23 °C

V max [VDC]	I max [A]	I hold [A]	I trip [A]	R initial min [Ω]	R initial max [Ω]	R 1hour max [Ω]	Max Time to trip [A]	Max Time to Trip [s]	Tripped Power Dissipation [W]	Order Number
60.0	40	1.1	2.2	0.15	0.25	0.38	5.5	8.2	1.50	PFRX.110
60.0	40	1.35	2.7	0.12	0.19	0.3	6.75	9.6	1.70	PFRX.135
60.0	40	1.6	3.2	0.09	0.14	0.22	8	11.4	1.90	PFRX.160
60.0	40	1.85	3.7	0.08	0.12	0.19	9.25	12.6	2.10	PFRX.185
60.0	40	2.5	5	0.05	0.08	0.13	12.5	15.6	2.50	PFRX.250
60.0	40	3	6	0.04	0.06	0.1	15	19.8	2.80	PFRX.300
60.0	40	3.75	7.5	0.03	0.05	0.08	18.75	24	3.20	PFRX.375

### Packaging Unit

PFRX.xxx Bulk (500 pcs.)  
 PFRX.110.2 - PFRX.160.2 Taped 34 cm Reel (1500 pcs.)  
 PFRX.185.2 Taped 34 cm Reel (1000 pcs.)

Time-Current-Curves

