DESCRIPTION: HD - 15 POS - MALE OVER MALE -0.625" CENTERS







ELECTRICAL CHARACTERISTICS

VOLTAGE:	250 VAC (rms) Max.
CURRENT RATING:	3 AMPS PER CONTACT
CONTACT RESISTANCE:	25 MilliOhms Max.
INSULATION RESISTANCE:	5000 MOhms Min.
dIELECTRIC WITHSTANDING:	1000 VAC (rms)
TOTAL MATING FORCE:	6.0 Kgf Max.
TOTAL UNMATING FORCE:	1.2 Kgf Min.
OPERATING TEMPERATURE:	-55°C TO +85°C

MATERIAL CHARACTERISTICS

HOUSING:	PA9T, UL94V-0, BLACK
CONTACTS:	COPPER ALLOY
SHELL:	SPCC
BOARDLOCK:	COPPER ALLOY
BRACKET:	ZINC ALLOY
SCREWLOCK:	COPPER ALLOY

PLATING CHARACTERISTICS

CONTACTS:	GOLD FLASH OVER NICKEL AT CONTACT AREA TIN PLATED OVER NICKEL AT THE SOLDER AREA
SHELL:	NICKEL PLATED
BOARDLOCK:	TIN PLATED
BRACKET:	NICKEL PLATED
SCREWLOCK:	NICKEL PLATED

189-YYY-613R577

- SERIES
- POSITIONS
  - H15
- GENDER
  - 61 = MALE OVER MALE
- SHELL PLATING
  - 3 = NICKEL
- RoHS COMPLIANT (HIGH TEMP. PROCESS)
- HARDWARE OPTIONS
  - 57 = 4-40 STAND OFFS/BOARD LOCKS
- PLATING OPTIONS
  - 7 = GOLD FLASH MATING AREA WITH TIN TAILS

RoHS Compliant

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp

DRAWN: J. KADEL		DATE: 07/05/2018	
CHECKED:		DATE:	
SCALE: NTS	SHEET 1 OF 1		REV 2
DWG NO. 189-H15-613R577			