



(b) NOTES:

1. RoHS COMPLIANT
2. METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
3. INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0; BLACK
4. CONTACTS: COPPER ALLOY; PLATING (SEE PART NO):
 - PLEASE ADD C for 30µm HARD GOLD over min. 50µm NICKEL
 - PLEASE ADD B for 20µm HARD GOLD over min. 50µm NICKEL
 - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
5. SEALING COMPOUND: PUR; BLUE
6. CAPACITANCE: 2 x 1300pF ± 20%
7. DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
8. CONNECTOR IS PART MARKED: 242□29100X CONEC ABC (see note 4)

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance		dim. in mm	scale: 2:1 (5:1)			
				material: SEE NOTES						
				drawn	08.02.13	Lehmenkühler		title: D-SUB PI FILTER FEMALE 9pos. SOLDER CUP		
				appd.	21.02.13	Fischer				
norm		d-old		24K1A158A		dwg no:				
2 x b	Ä4366	08.02.2013	Lehm.				DIN-A3			
a	Original						24K1A1391		sh: 1	
rev.	description	date	name	part no:		242□29100X (see note 4)				