



DESIGNED FOR USE WITH	.085 S.R.
CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.088
CONTACT	.024

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
02 ₂	REVISED	8/18/96	[Signature]

HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

COMPONENT	MATERIAL	FINISH
-----------	----------	--------

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES FRAC. ± 1/64 DEC. ±.005 ANGLES ± 1°	DRAWN BY CS DATE 11/10/77	AMP AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	CHECKED BY KWW DATE 11/10/77	
	APPD BY RMF DATE 11/17/77	

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE "OSSM" STRAIGHT CABLE PLUG - DIRECT SOLDER ATTACHMENT (40 GHz)		
	NO. A.P. 408-04776 (14-001)	SIZE B	CODE IDENT NO. 26805	1401-7985-00
		SCALE 10:1		REV 02 ₂

COPY IN PUERTO RICO

.XXX = in
XX.X = mm (REF)

CUSTOMER DRAWING

AMP PART # 1046477-1
SHEET 1 OF 1 REV A

SHEET 1 OF 1