



FIBER #	COLOR
1	BLUE
2	ORANGE
3	GREEN
4	BROWN

TRACE NUMBER{ TYCO ELECTRONICS XXXXXXXXXX
 TYCO ELECTRONICS P/N{ 6457078-1

△6 LABEL DETAIL

1. MAX INSERTION LOSS: 1.0 dB (1310nm)
- △2 PART SHIPPED WITH PIECE OF TAPE TO HOLD FIBER BUFFERS IN PLACE. TAPE TO BE REMOVED AFTER TERMINATING BUFFERED FIBER END OF ASSEMBLY.
3. PRODUCT AND PROCESSING MUST MEET REQUIREMENTS OF TYCO ELECTRONICS STANDARD 230-702.

LIGHTRAY MPX CONNECTOR FIBER PATH

1.000±0.051 [39.37±2.00]	6457078-1
L	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	KATHY HE	09DEC05	Tyco Electronics Corporation Harrisburg, PA 17105-3608
DIMENSIONS: METERS [INCHES]		CHK	J.BARRY	09DEC05	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	J.BARRY	09DEC05	NAME PIGTAIL, FIBER OPTIC, 4 FIBER SINGLEMODE BUFFERED FIBER, LIGHTRAY MPX(MALE)
0 PLC ± -		PRODUCT SPEC			
1 PLC ± -		APPLICATION SPEC			SIZE
2 PLC ± -					CAGE CODE
3 PLC ± -					DRAWING NO
4 PLC ± -					RESTRICTED TO
ANGLES ± -		WEIGHT	-	A2	00779
FINISH				C=6457078	
MATERIAL		CUSTOMER DRAWING		SCALE	1:1
				SHEET	1 OF 1
				REV	B