

#	Line 1	Line 2	Line 3	Line 4	QTY	Type
1	P.047ATCT-ND	ERJ-2BWFR047X	47mΩ • 1% • 0402 • .25W	±300PPM • -55 to +155°C	20	Thick Film - Low Resistance Type
2	P17368CT-ND	ERJ-2BWFR100X	100mΩ • 1% • 0402 • .25W	±300PPM • -55 to +155°C	20	Thick Film - Low Resistance Type
3	P17471CT-ND	ERJ-3BWFR047V	47mΩ • 1% • 0603 • .33W	±150PPM • -55 to +155°C	20	Thick Film - Low Resistance Type
4	P17478CT-ND	ERJ-3BWFR100V	100Ω • 1% • 0603 • .33W	±150PPM • -55 to +155°C	20	Thick Film - Low Resistance Type
5	P.047AQCT-ND	ERJ-6BWFR047V	47mΩ • 1% • 0805 • .5W	±200PPM • -55 to +155°C	20	Thick Film - Low Resistance Type
6	P17589CT-ND	ERJ-6BWFR100V	100mΩ • 1% • 0805 • .5W	±200PPM • -55 to +155°C	20	Thick Film - Low Resistance Type
7	P.047AUCT-ND	ERJ-8BWFR047V	47mΩ • 1% • 1206 • 1W	±100PPM • -55 to +155°C	20	Thick Film - Low Resistance Type
8	P.10AUCT-ND	ERJ-8BWFR100V	100mΩ • 1% • 1206 • 1W	±100PPM • -55 to +155°C	20	Thick Film - Low Resistance Type
9	P18935CT-ND	ERJ-B2CFR05V	50mΩ • 1% • 0612 • .75W	+150PPM • -55 to +155°C	20	Thick Film High Power - Wide Terminal Type
10	P18940CT-ND	ERJ-B2CFR10V	100mΩ • 1% • 0612 • .75W	+150PPM • -55 to +155°C	20	Thick Film High Power - Wide Terminal Type
11	P18936CT-ND	ERJ-B1CFR05U	50mΩ • 1% • 1020 • 1W	±150PPM • -55 to +155°C	20	Thick Film High Power - Wide Terminal Type
12	P18941CT-ND	ERJ-B1CFR10U	100mΩ • 1% • 1020 • 1W	±150PPM • -55 to +155°C	20	Thick Film High Power - Wide Terminal Type
13	P17098CT-ND	ERJ-MS4HF10MU	10mΩ • 1% • 2512 • 2W	±75PPM • -60 to +170°C	10	Thick Film Current Sensing - Metal Plate Type
14	P17099CT-ND	ERJ-MS6SFM50U	.5mΩ • 1% • 2526 • 5W	±75PPM • -60 to +170°C	10	Thick Film Current Sensing - Metal Plate Type
15	P17212CT-ND	ERJ-PA2F10R0X	10Ω • 1% • 0402 • .2W	±100PPM • -55 to +155°C	20	Thick Film - Anti-Surge Type
16	P17236CT-ND	ERJ-PA2F1003X	100KΩ • 1% • 0402 • .2W	±100PPM • -55 to +155°C	20	Thick Film - Anti-Surge Type
17	10.00BYCT-ND	ERJ-PA3F10R0V	10Ω • 1% • 0603 • .25W	±100PPM • -55 to +155°C	20	Thick Film - Anti-Surge Type
18	P100KBYCT-ND	ERJ-PA3F1003V	100KΩ • 1% • 0603 • .25W	±100PPM • -55 to +155°C	20	Thick Film - Anti-Surge Type
19	P18937CT-ND	ERJ-P06F10R0V	10Ω • 1% • 0805 • .5W	±300PPM • -55 to +155°C	20	Thick Film - Anti-Surge Type
20	P16060CT-ND	ERJ-P06F1003V	100KΩ • 1% • 0805 • .5W	±300PPM • -55 to +155°C	20	Thick Film - Anti-Surge Type
21	P18938CT-ND	ERJ-P08F10R0V	10Ω • 1% • 1206 • .66W	±100PPM • -55 to +155°C	20	Thick Film - Anti-Surge Type
22	P18939CT-ND	ERJ-P08F1003V	100KΩ • 1% • 1206 • .66W	±100PPM • -55 to +155°C	20	Thick Film - Anti-Surge Type
23	P47DCCT-ND	ERA-2AEB470X	47Ω • .1% • 0402 • .063W	±25PPM • -55 to +155°C	20	Thin Film - High Reliability Type
24	P100KDCCT-ND	ERA-2AEB104X	100KΩ • .1% • 0402 • .063W	±25PPM • -55 to +155°C	20	Thin Film - High Reliability Type
25	P47DBCT-ND	ERA-3AEB470V	47Ω • .1% • 0603 • .1W	±25PPM • -55 to +155°C	20	Thin Film - High Reliability Type
26	P100KDBCT-ND	ERA-3AEB104V	100KΩ • .1% • 0603 • .1W	±25PPM • -55 to +155°C	20	Thin Film - High Reliability Type
27	P47DACT-ND	ERA-6AEB470V	47Ω • .1% • 0805 • .125W	±25PPM • -55 to +155°C	20	Thin Film - High Reliability Type
28	P100KDACT-ND	ERA-6AEB104V	100KΩ • .1% • 0805 • .125W	±25PPM • -55 to +155°C	20	Thin Film - High Reliability Type
29	P47BCCT-ND	ERA-8AEB470V	47Ω • .1% • 1206 • .25W	±25PPM • -55 to +155°C	20	Thin Film - High Reliability Type
30	P100KBCCT-ND	ERA-8AEB104V	100KΩ • .1% • 1206 • .25W	±25PPM • -55 to +155°C	20	Thin Film - High Reliability Type