

AI 0,5 -10 WH

Order No.: 3201275

The figure shows the version AI 0,5-10 WH

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3201275>

Ferrule, Length: 16 mm, Color: white

Commercial data

GTIN (EAN)	4017918094775
sales group	B250
Pack	100 pcs.
Customs tariff	85369010
Weight/Piece	0.000093 KG
Catalog page information	Page 662 (CL-2009)

Product notes

WEEE/RoHS-compliant since:
01/01/2005

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Length (b)	16 mm
Color	white
Material	E-CU
Sleeve length	10 mm
Inner dimension of the insulating collar (d)	2.5 mm

Ferrule diameter	1.1 mm
Insulating collar thickness	0.25 mm
Sleeve wall thickness	0.15 mm


Certificates / Approvals



Certification CSA, UCSA

Diagrams/Drawings

Dimensioned drawing



AI 0,5 -10 WH Order No.: 3201275

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3201275>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;