

	1	2	3	4	5	6	7																																															
A	<p>Specifications:</p> <p>Material: Housing: Poly Carbonate(PC) UL94V-2 E919153 Contact blade: High strength copper alloy 100 micron Nickel underplated Plating type: 8% Phosphor Bronze Plating thickness: 50u" gold plated Operating temperature: -40°C to +125°C</p> <p>Electrical: Current rating: 250V AC max. at 2A Dielectric: 500V AC Insulation resistance: 500MΩ Termination resistance: 35mΩ Max after environmental tests</p> <p>Mechanical: Tensile Strength: 20LBS(89N) Min. Durability: 500 Mating Cycle</p> <p>Complies with FCC68/F</p>																																																					
B																																																						
C																																																						
D																																																						
E																																																						
F																																																						
G	<p>RoHS compliant Unit: mm</p> <table border="1"> <thead> <tr> <th>Scale</th> <th>Free TOLERANCE</th> </tr> </thead> <tbody> <tr> <td>X.X</td> <td>±0.20</td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> </tr> <tr> <td>X.XXX</td> <td>±0.05</td> </tr> <tr> <td>DIM</td> <td>TOL</td> </tr> <tr> <td>Angle</td> <td>±2°</td> </tr> <tr> <td>Angle</td> <td>TOL</td> </tr> </tbody> </table>							Scale	Free TOLERANCE	X.X	±0.20	X.XX	±0.10	X.XXX	±0.05	DIM	TOL	Angle	±2°	Angle	TOL																																	
Scale	Free TOLERANCE																																																					
X.X	±0.20																																																					
X.XX	±0.10																																																					
X.XXX	±0.05																																																					
DIM	TOL																																																					
Angle	±2°																																																					
Angle	TOL																																																					
H	<table border="1"> <thead> <tr> <th>1</th> <th>2</th> <th>3</th> <th>4</th> <th>5</th> <th>6</th> <th>7</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2</td> <td>3</td> <td>4</td> <td>5</td> <td>6</td> <td>7</td> </tr> <tr> <td>Angle</td> <td>±2°</td> <td>ⓐ Drawn</td> <td>Date</td> <td>Name</td> <td>Date</td> <td>Name</td> <td>Customer-F-No.</td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Modification</td> <td>13.06.2016</td> <td>Winnie</td> <td>13.06.2016</td> <td>Winnie</td> <td>ASSMANN WSW-No. A-MO 10/10-F50</td> </tr> <tr> <td colspan="5"> </td> <td>Drawing-No.</td> <td>Replace</td> <td>Sheet</td> </tr> <tr> <td colspan="5"></td> <td>ASS 7276 CO</td> <td>rev00</td> <td></td> </tr> </tbody> </table>							1	2	3	4	5	6	7	1	2	3	4	5	6	7	Angle	±2°	ⓐ Drawn	Date	Name	Date	Name	Customer-F-No.	Angle	TOL	Modification	13.06.2016	Winnie	13.06.2016	Winnie	ASSMANN WSW-No. A-MO 10/10-F50						Drawing-No.	Replace	Sheet						ASS 7276 CO	rev00		
1	2	3	4	5	6	7																																																
1	2	3	4	5	6	7																																																
Angle	±2°	ⓐ Drawn	Date	Name	Date	Name	Customer-F-No.																																															
Angle	TOL	Modification	13.06.2016	Winnie	13.06.2016	Winnie	ASSMANN WSW-No. A-MO 10/10-F50																																															
					Drawing-No.	Replace	Sheet																																															
					ASS 7276 CO	rev00																																																