

Stripping tool - WIREFOX-E 6SC - 1212705

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Stripping tool, for cables and conductors (especially for cables protected against short circuits and ground leakages) 1.5 - 6 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade


Product Description

Insertable stripping blades: 1212151 WIREFOX 4/SB, 1212153 WIREFOX 16/SB, and 1212152 WIREFOX 10/SB, direct replacement: 1212314 WIREFOX 6SC/SB

Why buy this product

- ✓ Flexible, adjustable limit stop for the stripping length
- ✓ Stripping tool with ergonomically shaped pliers.
- ✓ The stripping pliers feature an automatic adjustment mechanism for a wide range of different types of insulation and conductor diameters.
- ✓ Practical integrated wire cutter
- ✓ Flexible, adjustable limit stop for the stripping length
- ✓ Practical integrated wire cutter
- ✓ WIREFOX ... stripping pliers feature an automatic adjustment mechanism for a wide range of different types of insulation and conductor diameters

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 783606
GTIN	4046356783606

Technical data

Dimensions

Length (b)	191 mm
Width (a)	20 mm
Height (c)	90 mm
Cable diameter	1.5 mm ... 2.9 mm
Stripping length	18 mm

General

Color	black/green
Weight	136 g
Min. cross section	1.5 mm ²

Stripping tool - WIREFOX-E 6SC - 1212705

Technical data

General

Max. cross section	6 mm ²
--------------------	-------------------

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU x- DE.xx08.B.02974
-----	-------------------------------------------------------------------------------------	--------------------------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>