



NOTES:
 1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. ELECTRICAL SPECIFICATIONS (MOMENTARY CONTACT)
 VOLTAGE RATING: 125/250VAC
 CURRENT RATING: 10 AMPS (AC)
 4. ASSEMBLY IS RoHS COMPLIANT BY EXEMPTION

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
5	1	MOMENTARY SWITCH, 2P, 10 AMP (SPST NO)		
4	1	SWITCH BOOT	RUBBER	YELLOW
3	1	SWITCH BODY	NYLON	YELLOW
2	2	CONTACT PIN	Cu ALLOY	GOLD PLATED
1	1	PIN INSERT	PVC	YELLOW

NEW SALES DOC. EC NO: IPG2013-0880 DR: MHRSTONE 2013/01/22 CHKDK: JOZWIK 2013/01/25 APPR: JFMURPHY 2013/03/01	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES</td> <td>± .10</td> <td>± .004</td> </tr> <tr> <td>3 PLACES</td> <td>± .15</td> <td>± .006</td> </tr> <tr> <td>2 PLACES</td> <td>± 0.05</td> <td>± .002</td> </tr> <tr> <td>1 PLACE</td> <td>± 0.10</td> <td>± .004</td> </tr> <tr> <td>0 PLACE</td> <td>± .15</td> <td>± .006</td> </tr> </tbody> </table>		mm	INCH	4 PLACES	± .10	± .004	3 PLACES	± .15	± .006	2 PLACES	± 0.05	± .002	1 PLACE	± 0.10	± .004	0 PLACE	± .15	± .006	DIMENSION STYLE IN/MM	SCALE 1:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
		mm	INCH																					
4 PLACES	± .10	± .004																						
3 PLACES	± .15	± .006																						
2 PLACES	± 0.05	± .002																						
1 PLACE	± 0.10	± .004																						
0 PLACE	± .15	± .006																						
DRAWN BY: RSTONE 2013/01/22 CHECKED BY: K. JOZWIK 2013/01/25 APPROVED BY: JFMURPHY 2013/03/01	TITLE SWINGER 2P SWITCH SPST-NORMALLY OPEN		MATERIAL NO. 1300230001		DOCUMENT NO. SD-130023-005	SHEET NO. 1 OF 1																		

ANGULAR ± 5°
 DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

SIZE B

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION