



▲ LED SPECS	UNITS	YELLOW	BLUE
FORWARD CURRENT	mA	25	25
FORWARD VOLTAGE @20mA	VDC	1.95	3.3
LUMINOUS INTENSITY @ 10mA	mcd	232	585

- NOTES:**
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. RATING: 12VDC, 12mA; SPST
 5. CONTACT MATERIAL: GOLD
 6. CONTACT RESISTANCE: 50 MILLI-OHM MAX.
 7. INSULATION RESISTANCE: 500VDC, 100 MEGA-OHM MIN.
 - ▲8. OPERATING FORCE: 150±100GF
 9. OPERATING LIFE: 200,000 CYCLES
 10. OPERATING TEMP: -20°C TO +70°C
 - ▲11. LED COLORS: YELLOW, BLUE
 12. TRAVEL: 2.20mm±0.20
 13. 2002/95/EC (ROHS) COMPLIANT
 14. ▲DENOTES CRITICAL PARAMETER.



REV	PCR NO	DESCRIPTION	DATE	BY
B	19589	CHANGED DIMS: was 15.6 & 5.07	1/14/11	BGL
A	18147	New Release	6/18/08	rc

TITLE LP60A1ASYB				
SCALE	DATE	DR	DWG	REV
2=1	6/18/2008	rc	B220003	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED