

HDC enclosures HDC 24B TSLU 1PG21G

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

| | |
|------------|---|
| Type | HDC 24B TSLU 1PG21G |
| Order No. | 1662390000 |
| Version | HDC enclosures, Size: 8, Protection degree: IP 65, Cable entry from side, Plug housing, End-locking clamp, lower side, Standard, Size of cable entries: PG 21 |
| GTIN (EAN) | 4008190418915 |
| Qty. | 1 pc(s). |

HDC enclosures HDC 24B TSLU 1PG21G

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|--------|----------|------------|---------|
| Length | 135.5 mm | Width | 45.5 mm |
| Height | 61 mm | Net weight | 270 g |

Dimensions

| | | | |
|----------------------|--------|-----------------|--------------|
| Total length housing | 120 mm | Width housing C | 43 mm |
| Height of housing B | 61 mm | Cable entry | w. threading |

General data

| | |
|-----------------------|-------------------|
| Housing main material | diecast aluminium |
|-----------------------|-------------------|

Version

| | | | |
|------------------------------|--------------|--------------------------------|-------------------------------------|
| Internal thread | PG 21 | Design of housing | Cable entry from side, Plug housing |
| Size | 8 | Design | Standard |
| Top part/bottom part/lid | upper part | Design of locking system | End-locking clamp, lower side |
| Cable entry | w. threading | Size of cable entries | PG 21 |
| Number of cable entry on top | 0 | Number of cable entry sideways | 1 |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 2.0 | EC000437 | ETIM 3.0 | EC000437 |
| UNSPSC | 30-21-18-01 | eClass 4.1 | 40-02-06-14 |
| eClass 5.1 | 27-14-34-19 | eClass 6.2 | 27-26-12-03 |
| eClass 7.1 | 27-44-02-02 | | |

Approvals

Approvals



ROHS Conform

Downloads

| | |
|-------|--|
| PDF | 1662390000_HDC_24B_TSLU_1PG21G_STP_Blatt_1.pdf |
| IGES | 1662390000_HDC_24B_TSLU_1PG21G_STP.igs |
| VRML | 1662390000_HDC_24B_TSLU_1PG21G_STP.wrl |
| EPLAN | 1662390000.MZF |
| | 3-D model |

Data sheet...

**HDC enclosures
HDC 24B TSLU 1PG21G**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

